

Fife: Trough Urinal

Architects
Data File

Product Detail



Product: Fife
Code: FIFEXXX-XX

Issue: 1
Date: 07-03-25

Product description:

Fife Trough Urinal Pack. A complete, hygienic solution with a concealed stainless steel sparge flush, plastic cistern, and 2" domed waste.

Available in multiple sizes and configurations:
Centre waste (1200mm & 1500mm)
Left/Right waste (1200mm, 1500mm, 1800mm & 2400mm).

Universal top or rear water inlet. Configurable on site.


Product: Code: Length:

Fife	FIFE1200-LH	1200mm
Fife	FIFE1200-RH	1200mm
Fife	FIFE1200-CW	1200mm
Fife	FIFE1500-LH	1500mm
Fife	FIFE1500-RH	1500mm
Fife	FIFE1500-CW	1500mm
Fife	FIFE1800-LH	1800mm
Fife	FIFE1800-RH	1800mm
Fife	FIFE2400-LH	2400mm
Fife	FIFE2400-RH	2400mm

Technical Detail:

Material: <304> 1.4301 Stainless Steel
Gauge: 1.2mm
Inlet: 22mm Compression
Outlet: 2" BSP
Sparge: Supplied separately
Fixing: Wall-mounted

Lined Drawing:



Fife: Trough Urinal

Packaging Detail

Packing Dimensions Approx.:

1200 - L1250mm, W580mm, D325mm

1500 - L1550mm, W580mm, D325mm

1800 - L1850mm, W580mm, D325mm

2400 - L2450mm, W580mm, D325mm

Total Weight:

1200 = 22kg

1500 = 25kg

1800 = 28kg

2400 = 34kg

Materials Used:

Cardboard Box


Item Supplied with Product Labels



Fife: Trough Urinal

Installation Detail

- 1) **Unpack the Unit** – Remove all packaging materials.
 - 2) **Mark Installation Height** – Using a Spirit Level, determine and mark the required position and height on the wall.
 - 3) **Position and Mark Fixing Points** – Align the urinal with the marked height and mark the four fixing lug hole positions, ensuring it is level.
 - 4) **Drill Fixing Holes** – Drill holes suitable for wall fixings (fixings not supplied).
 - 5) **Prepare Inlet** – Knock out required inlet tab. If using a rear inlet, mark its position and drill through the wall accordingly.
 - 6) **Silicon Seal the Converter Bracket** – Apply silicon sealant to the face without the hole. Align the face with the hole to the inlet hole being used (top or rear).
 - 7) **Attach Sparge Pipe** – Secure the sparge pipe kit to the urinal. Fit the Sparge Pipe to the Compression Tee then fit to the urinal choosing the orientation required then attach the Inlet Coupler and tighten. Ensure sparge outlets are positioned towards back of trough. Locate each end of the Sparge Pipe through the slots in the Sparge Brackets then clip into position.
 - 8) **Secure the Unit** – Fix the urinal to the wall using appropriate fixings (fixings not supplied).
 - 9) **Install Waste Outlet** – Fit the supplied waste to the outlet, following enclosed instructions, and connect it to the on-site plumbing (2" BSP).
 - 10) **Mount and Connect Cistern** – Fix the cistern to the wall as per enclosed instructions, then connect the flush pipe to both the urinal inlet and cistern outlet.
 - 11) **Secure Pipework** – Attach all pipework to the wall using the supplied wall clips.
 - 12) **Connect Water Supply** – Connect the inlet water supply to the cistern as per the enclosed instructions.
 - 13) **Prime the Cistern** – Follow the instructions to prime the automatic cistern.
 - 14) **Test the Flush** – Once primed, the unit should flush automatically at set intervals.
 - 15) **Final Check** – Ensure all connections are secure and the unit is functioning correctly. The installation is now complete.
- Enjoy Your Product**



Fife: Trough Urinal

Spare Part Detail

- | | | | |
|-------------------|-----------------------------------|---|-----|
| 1) Cistern | - CISTERN-W9 | - Up to 1500mm | |
| 2) Down Pipe | - URDP30 | - Up to 1500mm | |
| 3) Cistern | - CISTERN-W13.5 | - Over 1500mm | |
| 4) Down Pipe | - URDP35 | - Over 1500mm | |
| 5) Domed Waste | - WK0408 | | |
| 6) Fix Kit | | | |
| i. | 62100P | - 1" Bsp Plastic Coupling Nut | x 1 |
| ii. | BS314 | - 22mm O'Ring | x 1 |
| iii. | SADL-22 | - 2 Pce Saddle Clip | x 2 |
| iv. | 999000Y | - Yellow Plastic Masonry Plugs | x 4 |
| v. | 9S90825 | - 8g x 1" SS Slotted Pan Head | x 4 |
| vi. | TEE003-RM | - Compression Tee | x 1 |
| vii. | COUPLER22-RM | - Inlet coupler | x 1 |
| viii. | COMP011 | - Rear Inlet Elbow (Supplied with Rear inlet versions only) | x 1 |
| ix. | Universal Inlet Bracket | | x 1 |
| 7) Sparge Pipes | - Cut to Length & Customer Fitted | | |
| i. | 1200 | - SPARGEPIPE-001 | x 1 |
| i. | 1500 | - SPARGEPIPE-005 | x 1 |
| ii. | 1800 | - SPARGEPIPE-002 | x 1 |
| iii. | 2400 | - SPARGEPIPE-003 | x 1 |
| 8) Extension Pipe | | | |
| i. | TUBE-30 | - 300mm x 22mm Dia x 0.7mm 304 water tube | |

1 & 2 or 3 & 4



6 Fixing Kit

7 & 8



5 Domed Waste



Care Of Your Product

HANDLING AND FIXING CAUTION

Take care when handling and fixing this product. Exposed edges of the stainless steel, including tap holes, upstand, overflows and wastes etc. may cause harm if handled without due caution. When using the fixing clips supplied with inset sinks avoid touching the two prongs on the area of the clip that grips the underside of the worktop.

TO THE STOCKIST

Please store products in a cool, dry area.

Sinks should, where possible be stood on their ends supported by battens with the bowl uppermost.

If sinks are nested with bowls inside one another, place some dry cushioning material between them to protect the surfaces.

TO THE INSTALLER

DO handle with care to avoid scuffs and scratches during installation.

DO check that edges of sinks are dead level so that water will flow off the draining board.

DO NOT over-tighten plumbing or other mechanical fixtures.

DO NOT remove the plastic protective film applied to certain products until all installation work has been completed.

DO NOT stand/kneel on the drainer of sinks.

DO NOT drop mortar, plaster or similar substances onto the stainless steel.

TO THE USER

Stainless steel will give you a lifetime of trouble free use as long as you follow a few simple rules. If it appears to mark, don't worry, it is usually not the steel, but something deposited on it, which has caused the apparent stain.

DO - wash the product before use.

DO - clean the product regularly, using JIF, Goddard's, or similar recommended cleaners. Follow the manufacturer's instructions carefully. Always rinse well with clean water and dry the surface with a soft cloth.

DO - use nylon or bristle brushes, not metal scrapers or wire brushes to loosen stubborn stains.

Never use wire wool pads, as they can scratch the steel.

DO - take care when handling sharp objects as they can scratch the surface of the steel. Any scratches will blend together over a period of time and become less noticeable with age. There is no detriment to the corrosion resistance or general performance of the material.

DO NOT - allow undiluted bleach to remain in contact with stainless steel (remember dishwasher powders, sterilising agents and similar products all contain chlorides). Black pit marks can result and permanent damage can be caused. Dilute to manufacturer's instructions and always rinse with clean water.

DO NOT - soak clothes in bleach solutions for long periods. Always rinse bowl with clean water after use.

DO NOT - leave such substances as Mortar, Grouting cement, soldering flux, photographic developing fluids, silver dip, denture liquids or food acids on the surface of the steel. Clean immediately and rinse well with clean water.

DO NOT - allow corrosive foodstuffs, such as fruit juices, damp salt, vinegar, mustards, pickles and mayonnaise to remain on the surface of the steel for long periods. Wash and rinse away.

DO NOT - let hard water cause a build-up of lime or chalk deposits which can sometimes be seen as a greyish film. Clean regularly with recommended cleaners to avoid this problem and always wipe dry with a soft cloth.

DO NOT - worry if the steel appears to rust. Usually it's deposits of wire wool scouring pads, plumbers swarf, particles from rusting storage tanks or other deposits on the surface which can be cleaned and rinsed away following your usual cleaning procedure. Bases of washing up bowls can harbour such deposits – check regularly.

DO NOT - use coarse grit cleaners or wire wool pads when cleaning the steel. They will scratch the surface.

DO NOT - leave carbon steel objects such as bottle openers, scissors, whisks and other kitchen objects standing on the surface for long periods, they can rust and leave marks.

DO PLEASE ENJOY YOUR NEW STAINLESS STEEL PRODUCT

Cleaning Regime

Problem

Routine Cleaning.

Oil & Grease Marks.

Stubborn marks, stains and light discoloration.

Heavy discoloration or heat tint.

Lime Scale

Corrective Treatment

Washing up liquid, all-purpose cleaning liquid, swab with cloth or sponge rinse well.

Degreasing fluid or cellulose thinners.

Mild abrasive creams (Sif / Shiny sinks).

Use metal polish (Brasso, Goddard's S/S Cleaner, Bar Keepers Friend) or a light non-metallic abrasive pad. Dura glit.

Apply descaler as instructed, agitate & allow to soak, re apply if not fully removed.
(Met-soak DX4920 or Hi-Phos)

Comments

Satisfactory on all surfaces.

Rinse with soap & water.

Heavy stains can be loosened by soaking with Metsoak or Hi-Phos. Rinse thoroughly after soaking as these products cause rust type marks if left.

Use only on grain finish surfaces and work in direction of grain as slight scratching will occur.

Bleach solutions including over the counter brands must only be used in dilution as instructed and thoroughly rinse immediately after application as chloride containing compounds will cause corrosion on all grades of stainless steel.

Rinse thoroughly after application and wipe dry as rust type stains can result if left undiluted on surface

There are also products on the market which help to reduce the marks left by fingers and hands one of which is 3m's stainless steel cleaner, also of help is baby oil very lightly applied to the surface.

SANITIZING URINAL BLOCKS

The use of these products must be done with the knowledge that they can in some instances react with other cleaning agents or on their own and cause scarring of the surface of the stainless steel. It is advisable to move them around the channel frequently to reduce their effect on one concentrated area.